



J Series Pendant Stations - Polypropylene Enclosures

One-Speed through Five-Speed Control plus Accessories

With Standard Cord Grip



J-6 Six-Button



J-8 Eight-Button



J-10 Ten-Button

Each enclosure includes a standard package of legend plates, cord grip, strain relief thimble and neoprene boots. The top accessory area on these enclosures will accept one two-button insert or two single buttons.

- Durable and lightweight Polypropylene Construction
- NEMA 1, 3, and 12
- Bright yellow for visibility and safety
- High resistance to solvents and impact
- CSA Approved
- Easy to read legend plates

| Dimensions and Weights | | | | | |
|--------------------------|------------------|-------|--------|-------------|---------------------------------------|
| Enclosure Catalog Number | Dimension-Inches | | | Weight Lbs. | Accommodates Cable Diameter (Inches*) |
| | Width | Depth | Length | | |
| J-6 | 3-3/4 | 3-3/4 | 16 | 2-1/2 | .688 - 1.250 |
| J-8 | 3-3/4 | 3-3/4 | 20 | 3 | .688 - 1.250 |
| J-10 | 3-3/4 | 3-3/4 | 24 | 3-1/2 | .688 - 1.250 |

* Specify Cable Diameter

| Cord Grip and Bushings for J Series Pendants | |
|--|-----------------------------------|
| Catalog No. | Cord Grip Cable Diameter (Inches) |
| RPC-CG4 | .625 - .750 |
| RPC-CG5 | .750 - .875 |
| RPC-CG6 | .875 - 1.000 |
| RPC-CG7 | 1.000 - 1.125 |
| RPC-CG8 | 1.125 - 1.250 |

Pictures are for illustration purposes and may not represent actual product. Duct-O-Wire® recommends installation of an Emergency Stop on all Pendants.